

Dane do obliczeń :

Źródła punktowe

Nr X[m] Y[m] z[m] Pma Symbol

=====

1	473.0	355.0	1.0	73.4	P1
2	484.5	346.0	1.0	78.0	P2
3	496.0	337.0	1.0	76.6	P3
4	507.0	348.0	1.0	68.8	P4
5	517.0	361.0	1.0	68.8	P5
6	531.0	362.0	1.0	71.5	P6
7	540.0	374.0	1.0	69.6	P7
8	492.7	359.1	6.0	75.9	E2
9	497.5	365.4	6.0	75.9	E3
10	502.3	371.1	6.0	75.9	E4
11	506.4	376.6	6.0	75.9	E5
12	523.7	397.3	6.0	75.9	E6
13	528.0	403.0	6.0	75.9	E7
14	533.0	409.0	6.0	75.9	E8
15	535.0	382.0	1.0	64.0	P8
16	546.0	396.0	1.0	64.0	P9
17	557.0	410.0	1.0	64.0	P10
18	568.0	424.0	1.0	64.0	P11
19	559.0	431.0	1.0	76.1	P12

=====

Źródła typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr X1[m] Y1[m] X2[m] Y2[m] X3[m] Y3[m] X4[m] Y4[m] h0[m] h[m]

=====

1	478.8	356.7	530.2	420.3	539.8	413.1	488.4	348.8	0.0	8.0
---	-------	-------	-------	-------	-------	-------	-------	-------	-----	-----

=====

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr źródła A 63 125 250 500 1000 2000 4000 8000 wsp.odb.

=====											
1	sc.1	L wew	87.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	87.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	87.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	87.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	87.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
=====											